1. Handling

.

Unit Volume / Weight

Unit Ref :	VRKNC-1220
Volume :	0.329 m ³
Weight :	775 kg

- Weight is based on 2,350 kg/m³ .
- Lifting system is by means of a 16mm dia. inverted 'V' hook using lifting chains or similar certified lifting system. Hook certified to : (LOLER 1998), (PUWER) 1998 (The spherical pin anchor is used for production purposes only).

IMPORTANT NOTE :

Prior to lifting older / pre-used blocks, check the lifting pin for wear / corrosion and check the block for cracks. If the block is cracked or the pin is worn, it could fail when lifting.

2. Concrete

- Characteristic 28 day cube strength = 50 N/mm² min.
- Concrete is Class A1 Fire Resistant in accordance with clause 4.3.4.4 of EN 13369

3. Manufacture


- Manufactured to : BS EN 13369 : 2013
- BS EN 13670 : 2009 Tolerances to :

4. Physical & Chemical Properties

- Appearance : Grey in Colour
- Other Chemical Properties : Not Applicable

5. Design





120 85

195

120

ø16mm

Rebar

Lifting

Hook.


150


typ. 5

75

Natural Stone

Finish.





							ŀ				-		
					TITLE Vee-Rock™ Interlocking Concrete Block 1220mm x 585mm x 610mm Natural Stone Faced (notched Corner) Elite Product Code : VRKNC-1220					ELITE PRECAST CONCRETE LTD HALESFIELD 9, TELFORD SHROPSHIRE TF7 4QW			ELITE PRECAST CONCRETE
										www.eliteprecast.co.uk			
0	22.06.23	First Issue.	CTC	RMD	-			DATE	22-06-23		SCALE 1.15	DRG EPC-VRK-006	
REV	DATE	REASON FOR ISSUE	DRN	APP				DATE	22-00-23				

500

990

500

-(;;;)

150

75