

Declaration of Performance

DOP 2

This declaration of performance relates to the following precast concrete components for use in a manhole or in an inspection chamber:

Cover Slabs
DN900 to DN3000 & LN1200 x WN750

The intended use is to permit access to, and allow aeration of, drain or sewer systems for the conveyance of sewage, rainwater and surface water under gravity or occasionally under low head of pressure, mainly installed in areas subjected to vehicular and / or pedestrian traffic

The products are manufactured by:

Elite Precast Concrete Limited
Halesfield 9,
Telford
Shropshire TF7 4QW

The system of attestation of conformity:

System 4

These products are covered by the harmonized standard:

BS EN 1917:2002

Essential characteristic	Performance	Harmonised technical specification
Opening sizes	As clause 5.5.3 of BS 5911-3:2022	EN 1917:2002 clause 3.1.1.6
Mechanical resistance	Characteristic compressive strength of concrete = 40N/mm ² (40MPa) DN900 to DN1200 & LN1200 x WN750 Vertical strength 300kN DN1350 to DN1800: Vertical proof load 1 x 250kN DN2100 to DN3000: Vertical proof load 2 x 250kN	EN 1917:2002 clause 4.2.2.2 EN 1917:2002 clause 4.3.6 BS5911-3:2022 clause 6.2 BS5911-3:2022 clause 6.2
Load bearing capacity of any installed steps	N/A - there are no installed steps in these products	EN 1917:2002 clause 4.3.7
Water tightness	N/A	
Durability	Adequate for normal serviceability conditions	EN 1917:2002 clause 4.3.10



Elite Precast Concrete Limited
Unit O, Halesfield 9, Telford, Shropshire TF7 4QW
Tel: 01952 588 885 | sales@eliteprecast.co.uk
www.eliteprecast.co.uk



**ELITE PRECAST CONCRETE LIMITED,
HALESFIELD 9, TELFORD, SHROPSHIRE TF7 4QW
13**

EN 1917:2002

**Precast component for use in a manhole or in an inspection chamber
Reinforced concrete shaft/chamber section**

Water tightness:	No leakage of joint at 50kPa (0.5 bar) internally
Mechanical resistance:	Vertical strength 300kN (120kN proof load)
Opening sizes:	DN900 - 600 x 600 or 675 x 675 DN1050 - 600 x 600 or 675 x 675 or 750 x 750 DN1200 to DN3000 - 600 x 600 or 675 x 675 or 750 x 600 or 1200 x 675 LN1200 x WN750 - 600 x 600 or 675 x 675 or 750 x 600
Durability:	Adequate for normal serviceability conditions

Signed for and on behalf
of the manufacturer:



Richard Doody
Commercial Director

Dated 08.08.2024



Elite Precast Concrete Limited
Unit O, Halesfield 9, Telford, Shropshire TF7 4QW
Tel: 01952 588 885 | sales@eliteprecast.co.uk
www.eliteprecast.co.uk