

Max. Permissible Impact Loads Allowable impact load speed based on:-

Vehicle (Maximum operating weight 20t)

Total allowable deflection - 100mm.

NOTE:-

Impact loads are the expected loads imposed on the wall by loading shovels, backhoes, buckets etc. carrying out NORMAL procedures of loading and unloading bays.

NOTE:-


Wall has <u>not</u> been designed for retained material to be compacted by vehicle driving over or on top of the retained material.


NOTES:-

- 1. The contractor should take all necessary measurements on site.
- 2. All dimensions shown on this drawing are approximate and for structural calculation purposes only.
- 3. Dimensions on this drawing should not be used for fabrication purposes.
- 4. Do not scale this drawing.
- 5. This drawing should be read in conjunction with the calculations.


IMPORTANT NOTE

The existing slab and ground have not been investigated by CLP structures, the pressures exerted on the ground and slab are shown on this drawing, however it is up to the client to satisfy himself that the existing ground and slab are adequate to support these loads.





Bearing Pressure
Directly Beneath Wall




Bearing Pressure
Beneath 175mm slab

NOTE:-

The bearing pressure beneath the wall is shown below. It is up to the client to ensure the ground and slab is adequate, alternatively a foundation may be designed to suit allowable ground bearing pressures if required.


Bearing Pressures Load Case 2.

(1:25)




Bearing Pressure


Directly Beneath Wall




Bearing Pressure
Beneath 175mm slab

Bearing Pressures Load Case 1. (1:25)








Bearing Pressure
Beneath 175mm slab

Bearing Pressures Load Case 3. (1:25)





Date June 16

495-04

А3