

White Goods Storage Bays – Design Guidance Notes.

Where white goods are stacked up adjacent to an Elite Legato block wall the following guidelines apply:-

- 1. The maximum height of a single skin Legato block wall with should be 4.8m (6 blocks).
- 2. The maximum stacking height of white goods should be approximately 3m.
- 3. The wall is designed as a barrier to enclose loose waste, and to act as a fire barrier. It should be noted that the wall is not designed to retain the white goods in the event of a sudden collapse or instability of the stacked white goods.
- 4. White goods should be stacked up against the walls to ensure that the stacks remain stable and sudden collapse of the stack cannot occur, a maximum distance between the stack and wall of 100m is recommended.
- 5. White goods should not be allowed to fall against the wall under any circumstances.
- 6. The stack should be inspected on a fortnightly basis to ensure that the stack is self supporting with no signs of leaning, bowing or possible collapse.
- 7. The block walls should also be inspected on a monthly basis to ensure that that no damage or movement has occurred.

Chris Lyons AMIStructE. BTech. leng. Director

CLP Structures Ltd. Cranmore View, Fairview, Main Rd, Temple Cloud, Bristol. BS39 5DD. TEL: 0117 3706357 EMAIL: <u>mail@clp-structures.co.uk</u>